







casaterradesign

CAPTURE SPECIFICATIONS

Design no.	2472	
Application	• upholstery	
Composition	85% New Zealand wool / 15% polyamide	
Weight	g/lm	475
	oz/lin.yd	15.32
Width	cm	140
	inches	55
Abrasion	rubs martindale (EN ISO 12947-2)	200,000
	rubs martindale (ASTM D4966) (heavy duty upholstery)	200,000
Pilling	scale 1-5, max. 5 - EN ISO 12945-2	4-5
Light fastness	scale 1-8, max. 8 - EN ISO 105-B02	5-7
Rubbing fastness	scale 1-5, max. 5 - EN ISO 105x12 (dry/wet)	4-5/4-5
Maintenance	dry cleaning P(S)	
		
US ACT	 <u>CA TB 117-2013</u>	pass
	 <u>AATCC 8 or 116 Dry/wet crocking</u>	pass
	 <u>AATCC 16 Light fastness</u>	pass
	 <u>ASTM D4966 Martindale (heavy duty)</u>	pass
	 <u>ASTM D4970 Pilling</u>	pass
US ACT	Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan	
Acoustic test air flow resistance	• <u>EN 29053 & ISO 9053-1 (airflow resistance)</u>	•
Flammability	• <u>BS EN 1021 1&2 Cigarette and Match</u>	•

- BS 5852 Part 1 0,1 Cigarette & Match, The Furniture and Furnishing Regulations 1988
- Class Uno UNI 9175 Class 1 I EMME
- CA TB 117-2013
- Will also pass other flammability standards. Flame retardant performance is dependent upon the foam used.
- Contains no flame retardant chemicals.

Flammability with flameretardant treatment

- BS 5852 Crib 5 (flame retardant) •

Certificates

Complete list

Environment OEKO-TEX® STANDARD 100
EU Ecolabel

Design Cenk Kivrikoglu

Colours Cenk Kivrikoglu